



Pressure Seals, Inc.

Phone: (877)-PSI-SEAL Toll Free
 Thousands of Seals, O-Rings, and U-Cups
 World-Class Service since 1976!



900 Sizes for Straight Thread Tube Fittings					
I.D. (inches)				C/S	
No.	Min.	Mean	Max.	(In.)	Tolerance
-901	0.180	0.185	0.190	0.056	+or- 0.003
-902	0.234	0.239	0.244	0.064	+or- 0.003
-903	0.296	0.301	0.306	0.064	+or- 0.003
-904	0.346	0.351	0.356	0.072	+or- 0.003
-905	0.409	0.414	0.419	0.072	+or- 0.003
-906	0.463	0.468	0.473	0.078	+or- 0.003
-907	0.523	0.530	0.537	0.082	+or- 0.003
-908	0.635	0.644	0.653	0.087	+or- 0.003
-909	0.697	0.706	0.715	0.097	+or- 0.003
-910	0.746	0.755	0.764	0.097	+or- 0.003
-911	0.854	0.863	0.872	0.116	+or- 0.004
-912	0.915	0.924	0.933	0.116	+or- 0.004
-913	0.976	0.986	0.996	0.116	+or- 0.004
-914	1.037	1.047	1.057	0.116	+or- 0.004
-916	1.161	1.171	1.181	0.116	+or- 0.004
-918	1.343	1.355	1.367	0.116	+or- 0.004
-920	1.461	1.475	1.489	0.118	+or- 0.004
-924	1.706	1.720	1.734	0.118	+or- 0.004
-928	2.072	2.090	2.108	0.118	+or- 0.004
-932	2.319	2.337	2.355	0.118	+or- 0.004

Please be advised that all specifications are provided for general guidance only and should be confirmed by a Pressure Seals representative. For assistance, please call us at (860) 282-9100.

Copyright 2016 Pressure Seals, Inc. All rights reserved. Revised: 5/13/97