


Pressure Seals, Inc.

Phone: (877)-PSI-SEAL Toll Free Thousands of Seals, O-Rings, and U-Cups World-Class Service since 1976!



TFE Wearband Tape



Wearband strip is supplied in 2 materials: 60% bronze filled teflon and phenolic. Phenolic strip is supplied by the foot in coils and the teflon strip is supplied by the inch in roll form.

Be aware that many competitors supply teflon strip with less or no bronze content and that nothing less should be used for heavy duty hydraulic applications.

Lightly filled teflons are fine for light duty pneumatic applications. Phenolic strip offers excellent compressive strength, but may be harder to form in some applications. 60% bronze filled teflon strip will form to any size easily and can be skive cut to almost any width and thickness. For full rolls or coils, call sales for pricing, availability and length.

Part	Width		Wall
Number	D		С
WBTAPE-0375-062BTFE	3/8	Χ	1/16
WBTAPE-0375-125BTFE	3/8	Χ	1/8
WBTAPE-0500-062BTFE	1/2	Χ	1/16
WBTAPE-0500-093BTFE	1/2	Χ	3/32
WBTAPE-0500-125BTFE	1/2	Χ	1/8
WBTAPE-0562-125BTFE	9/16	Χ	1/8
WBTAPE-0750-062BTFE	3/4	Χ	1/16

Part	Width		Wall
Number	D		С
WBTAPE-0750-093BTFE	3/4	Χ	3/32
WBTAPE-0750-125BTFE	3/4	Χ	1/8
WBTAPE-1000-062BTFE	1	Χ	1/16
WBTAPE-1000-093BTFE	1	Χ	3/32
WBTAPE-1000-125BTFE	1	Χ	1/8
WBTAPE-1500-125BTFE	1 1/2	Χ	1/8

Metric Wearband Tape

Part	Width		Wall
Number	D (mm)		C (mm)
WBTAPE-0221-098BTFE	5.6	Χ	2.5
WBTAPE-0311-157BTFE	7.9	Χ	4.0
WBTAPE-0374-157BTFE	9.5	Χ	4.0
WBTAPE-0381-098BTFE	9.7	Χ	2.5
WBTAPE-0472-079BTFE	12.0	Χ	2.0

Part	Width		Wall
Number	D (mm)		C (mm)
WBTAPE-0571-157BTFE	14.5	Χ	4.0
WBTAPE-0591-098BTFE	15.0	Χ	2.5
WBTAPE-0787-098BTFE	20.0	Χ	2.5
WBTAPE-0984-098BTFE	25.0	Χ	2.5

Phenolic Wearband Tape

Part Number	Width D (mm)		Wall C (mm)
WBTAPE-0220-098P	5.6	Χ	2.5
WBTAPE-0381-098P	9.7	Х	2.5
WBTAPE-0511-098P	13.0	Х	2.5

Part	Width		Wall
Number	D (mm)		C (mm)
WBTAPE-0591-098P	15.0	Χ	2.5
WBTAPE-0787-098P	20.0	Χ	2.5
WBTAPE-0984-098P	25.0	Χ	2.5

Phone: (877)-PSI-SEAL Toll Free, In CT: (860) 282-9100, Fax: (860) 282-9001




Pressure Seals, Inc.

Phone: (877)-PSI-SEAL Toll Free Thousands of Seals, O-Rings, and U-Cups World-Class Service since 1976!



Nylon Female Center Bearings



Bearings are made from glass filled nylon with excellent compressive strength. They are used for piston applications between sets of vee packing.

	В	Bearing Size			Packing Size		
	Inside	Outside		Inside		Outside	
Part	Diameter	Diameter	Height	Diameter		Diameter	
Number	Α	В	D				
FCB-2500-625	1 1/2	2 1/2	5/8	2	Χ	2 1/2	
FCB-3000-625	2	3	5/8	2 1/2	Х	3	
FCB-3500-625	2 1/2	3 1/2	5/8	3	Х	3 1/2	
FCB-4000-625	3	4	5/8	3 1/2	Х	4	
FCB-6000-750	4 3/4	6	3/4	5 1/4	Х	6	
FCB-7000-1000	5 3/4	7	1	6 1/4	Χ	7	

	Bearing Size			Packing Size		Size
	Inside	Outside		Inside		Outside
Part	Diameter	Diameter	Height	Diameter		Diameter
Number	A (mm)	B (mm)	D (mm)	(mm)		(mm)
FCB-80MM-17	55	80	17	65	Χ	80
FCB-90MM-17	65	90	17	75	Χ	90
FCB-100MM-17	75	100	17	85	Χ	100
FCB-110MM-17	85	110	17	95	Χ	110
FCB-115MM-17	90	115	17	100	Χ	115
FCB-125MM-17	100	125	17	110	Χ	125
FCB-150MM-17	125	150	17	135	Χ	150

Phone: (877)-PSI-SEAL Toll Free, In CT: (860) 282-9100, Fax: (860) 282-9001